PISTOL RED DOT SIGHT

User Manual



Feyachi®

Specification



Pistol Red Dot Sight

Objective Aperture	22.6mm
Parallax	≤2 MOA
Adj. Range	+/-50 MOA
Click Value	1 MOA/Click @ 50yds
Protection Level	IPX7
Shake Awake	8 Minutes
Size	1.69 x 1.14 x 1.02 inch
Weight	1.09 Oz

Inside the box



1 x Cleaning Cloth | 1 x User Manual | MOS Adaptor Plate | 3 x Wrenches | 2 x CR 2032 Batterys

How To Use?

1. Install the battery

After opening the battery guard with wrench, insert the CR2032 battery, and then lock the battery guard.





2. Turn on the red dot

Press the +/- button on the side to turn on the power and return to the previous brightness, there are 11 kinds of brightness can be adjusted.

Press and hold any button for 3 seconds to turn off the power.



3. Shake Awake

After 8 minutes of inactivity, the red dot will go into sleep.

Just a slight vibration to wake up the red dot



4. MOS Adaptor Plate

In addition to the Picatinny base thought also comes with a MOS adapter plate, 0.45in footprint compatible to better fit Glock and other pistols slide holster.

Zeroing

With the sight mounted, rest the equipment on a solid support and aim at a target 50 yards away. Test shots should be done in the same conditions to achieve maximum accuracy for adjustment, for which the use of equipment rest for firing is recommendable. Each click adjustment moves the point of impact by 1 MOA (approximately 1/2" = at 50 yards).

Elevation & Windage Adjustment

Adjust the elevation and windage to the zero position.



Notice

Feedback from some customers states that the sights are blurry or ⅢI shows double images. Please don't worry, It just needs 3~5 minutes to preheat when you first use it. (Just turn it on and let it stay for 3~5 minutes). Then it will show clearly.If it still results in the same, please do not hesitate to let us know before you low rating, we will try our best to help you out.

If it still results in the same, please do not hesitate to let us knowbefore you low rating, we will try our best to help you out.

Warranty

Within 12 months of purchase: Return to Feyachi for repair orreplacement. This warranty does not cover normal wear and tear,modifications, misuse, disintegrations, negligence, accidents, impropermaintenance, or repair by anyone other than an Authorized retailer orFeyachi Itself.

Contact

info@feyachi.com
www.facebook.com/Freoutdoor
www.feyachi.com



Red Dot Sight

MOS Adaptor

Picatinny Base

Feyachi®